



# **Touchless Automatic Car Washer**

Car Washing Made Easy





with Optional integrated UNDER CHASSIS WASHER



## **Smart Features**

With STORM, ATS ELGI brings a simple and pragmatic approach to car washing. STORM enables a quick wash in less than 3 minutes. The ultrasonic sensors, the corrosion resistant design, the torque limiter, the foam stoppers and the integrated under chassis washer makes STORM the product to reckon with.



### Key features and benefits

- Automatic vehicle length sensing
- Quick wash time
- Torque limiter stops the machine on any obstruction
- Soft PE foam stopper for enhanced vehicle safety
- Low water consumption compared to a conventional wash
- Low power consumption compared to a conventional wash
- Optional Integrated under chassis washer

Technical Specifications	
Machine Type	Overhead carriage Dual swing arm type
Required space, mm ( L x W x H )	7000 x 3800 x 3100
Overall dimension, mm ( L x W x H )	6560 x 3710 x 3010
Maximum washable dimension of car, mr ( $L \times W \times H$ )	n 4900 x 2300 x 1900
Operating system (water) pressure, bar	16
Water consumption per car, litres*	80 - 105
Shampoo consumption per car, ml*	40 - 60 (Recommended dilution: 1:135 )
Cycle time per car, min* (Excluding manual wiping)	2 - 2.7
Input supply	3Ø, 355V - 455V, 50 Hz
Total connected load, kW	5.1
Total operational load, kW	4.34
Power consumption per car, kWh	0.08 - 0.1
	*D !! .! !! !!

### **Under Chassis Washer**



Low water consumption 24 litres per car



High operating pressure of 55 bar for effective cleaning



Rotating dual nozzle for better reach

#### Key features and benefits

- High operating pressure (water) of 55 bar
- Quick wash time: 1 minute per car
- Low water consumption compared to a conventional wash
- Low power consumption per car: 0.1 kWh
- Automatic vehicle length sensing

Technical Specifications	
Machine Type	Rotating Nozzle with Moving Carriage
No. of Nozzle	2
No. of cycles to clean	1 No (2 pass)
Operating Pressure (water), bar	55
Water Consumption per car, Liters	24
Input Supply	3Ø, 355V - 455V, 50 Hz
Total Power required, kW	5
Power Consumption per car, kWh	0.1
Equipment Finish	Hot Dip galvanized
Overall Dimension, mm	5410 X 641 X 207





#### ATS ELGI Ltd.,

Private Industrial Estate, Kurichy, Coimbatore - 641021, India Tel: +91-422-2589999, Fax: +91-422-2589800

Email: enquiry@ats-elgi.com Visit us at: www.ats-elgi.com

**Ahmedabad** - 3774109 **Bangalore** - 22240674 **Bhopal** - 2578281 **Chennai** - 28172599 **Hyderabad** - 27768326 **Jaipur** - 2375595 **Kochi** - 2360155 **Kolkatta** - 22834270



