

WASHING EQUIPMENTYour trustworthy cost-effective washing partner





High Pressure Washers

The ATS ELGI series of reciprocating pumps are designed with advanced engineering technique to fulfill the most exact requirements of contemporary users. They bear a fine reputation for both quality and reliability as well as minimum maintenance and service.

Every component in a ATS ELGI reciprocating pump is subject to stringent quality assurance tests before final assembly.

ATS ELGI reciprocating pumps find extensive use in service stations, garages, boiler feeders, steel mills, hydraulic presses, mining, breweries, spraying, food processing and numerous other applications.

Single and Triple plunger type pumps are offered with single/twin guns with hose either on an integral tank or on a sturdy base frame.



Advantages

- **Direct Driven**
- Trigger Gun to reduce impact pressure at different applications
- Low Maintenance Cost
- Jet/Spray options for Engine Compartment Wash
- Positive suction Pump

Technical Specification

	LL 03 022	P 12/28	P 36/30	P 36/40	P 76/40	HL 03 045 (New Gen TPP)
Displacement, lpm	26.3	11.5	17.5	50	100	17
Delivery per Gun, lpm	11.5	11	17	22	45	17
No. of Guns	2	1	1	2	2	1
No. of Plungers	1	3	3	3	3	3
Operating Pressure, Kgf/cm ²	22	18	45	40	40	45
Motor Power, HP	3	1	2.5	10	15	3
Pump Speed, rpm	350	470	340	400	340	1440
Type of Mounting	Base / Tank	Base	Base	Base	Base	Base
Suction Type	Negative	Negative	Negative	Negative	Negative	Positive



Private Industrial Estate, Kurichy, Coimbatore - 641021, Tamil Nadu, India.

Tel: +91-422-2589999 | Email: enquiry@ats-elgi.com

Visit us at: www.ats-elgi.com

Toll-free number: 1800-425-3544

